

SX shown with Pearl shell



SX shown with Pearl shell, Coastal Gray cabinet and Polymer step



| Seating Capacity | 3 adults |
|-----------------------------|---|
| Dimensions | 6' x 6' x 33"/1.83m x 1.83m x .84m |
| Water Capacity | 285 gallons/1,075 liters |
| Weight | 720 lbs./325 kg dry; 3,620 lbs./1,640 kg filled* |
| Spa Shell Options | Pearl or Desert |
| Cabinet Options | Coastal Gray, Espresso or Teak |
| Jets - 17 | 1 Moto-Massage° jet 16 Directional Precision° jets |
| Waterfall | n/a |
| Jet Pump 1 | Wavemaster® 6200; Two-speed 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque |
| Jet Pump 2 | n/a |
| Circulation Pump (Optional) | SilentFlo 5000° |
| Water Care System | FROG® In-Line Cartridge Ready |
| Ozone System (Optional) | FreshWater® III Corona Discharge |
| Control System | IQ 2020° 115v/20 amp** (Includes G.F.C.I. protected power cord) or 115v/30amp*** or 220v/50amp***, 60Hz |
| Lighting | Blue LED light, dimmable; Splendors® multi-colored LED light, dimmable (optional) |
| Heater | No-Fault® 1000w/115v |
| Energy Efficiency | FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law |
| Effective Filtration Area | 30 sq. ft., top loading |
| Vinyl Cover | 3" to 2" tapered, 1 lb. density foam core Ash, Caramel or Chestnut |
| Cover Lifter (Optional) | CoverCradle®, CoverCradle II, Lift 'n Glide® |
| Steps (Optional) | Everwood® or Polymer Coastal Gray, Espresso or Teak |

- Includes water and 3 adults weighing 175 lbs. each.
 Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.
 G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode.
 Export models available in 230v, 50Hz, 1000w heater.

From the makers of

